



The GMP-200L is a 32" tall cart that holds a single display up to 65" or dual displays up to 55". Comes standard with 10RU 19" rack mount bracket in front and rear, 6 port APC® surge protector, adjustable shelf and has an interior depth of 14". Includes universal screen mounting system and set-top camera mount. Choose TT-1 or TT-2.

Please include model number of screen(s) when ordering.

## GMP - 200L - TT1/ TT2

SOLID STEEL CARTS

### The most **FEATURES** on the market:

- ▶ TT-1 for use with single display
- ▶ TT-2 for use with dual displays
- ▶ One adjustable interior rack mounted shelf
- ▶ 6 Port APC® surge protector
- ▶ Cable management features
- ▶ Tempered, tinted locking front glass door
- ▶ Bolted rear panel for easy access to equipment
- ▶ Standard 19" front and rear rack mount brackets, 10RUs of space
- ▶ Standard adjustable v/c camera platform
- ▶ 32" Height for optimal face to face communication
- ▶ Standard 4" double truck ball bearing casters, two with brake
- ▶ 100% Solid steel construction

### Choose your **OPTIONS**:

- ▶ Additional rack mount shelf (US-1)
- ▶ Rack mounted M-Audio® speaker module (PSM-200)
- ▶ Heavy duty 6" caster upgrade
- ▶ Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ▶ GM-9000 to accommodate deeper equipment
- ▶ 6 Port rack mount APC® surge protector (RCK-PWR)
- ▶ Custom cut Rack Shelf for Lifesize®, Polycom® and Tandberg® codecs
- ▶ Revolabs® Shelving System in various configurations for wireless microphone integration

### DIMENSIONS:

Load Capacity: 350 lbs.

#### EXTERIOR

Height - 32"

Width - 76"

Depth - 27 1/2"

#### INTERIOR

Height - 17 1/2"

Depth - 14"

Rack to Glass - 1 7/8"

Rack Width - 19"

Rack Units - 10 RUs

#### SHIPPING BOX (Palletized)

Length - 48"

Width - 40"

Height - 84"

Ship Weight - 255 lbs



Available for immediate shipping



Ask about customized design  
and prototype capabilities

Furniture Engineered For Today's Technology

